

ROLLEX MEDICAL (AUST) PTY LTD

PO Box 170 | Mt Kuring-gai 2080 | Sydney, NSW | Australia

Phone: +61 2 9457 6144 | Fax: +61 2 9457 6516

Email: sales@rollexmedical.com | www.rollexmedical.com.au

Model Variations

MATOS Aria Eco 220 R – Solid Door MATOS Aria Eco 220 R/G – Glass Door





The MATOS® Aria Eco fridge series is a new range of cost-effective European-built Medical and Vaccination Refrigerators featuring the latest technology in controllers and compressors for accurate temperature stability.

Advanced Controller

Featuring the Carel soft touch controller - accurate to 0.1°C with min/max readings at the touch of a button.

Lock Fitted as Standard

Maintains security and ensures the unit can only be opened by authorised personnel.

Cost-Effective

Built with a High Impact Polystyrene Interior to provide a robust and in-expensive range of refrigerators.

Solid or Glass Door Options

Solid or glass door options enabling you to select the format which best suits your requirements. Glass doors are double glazed, toughened safety-glass with argon gas between panels for better insulation.

Auto Defrost

The advanced controller initialises a regular defrost sequence to decrease the chance of ice build-up while maintaining the temperature below 8°C.

Extended Warranty

Standard 12 month warranty however an extended warranty option is available subject to Terms and Conditions

CCTC / QCPP Certified

CCTC and QCPP Approved Vaccine Pharmacy Graded Refrigerator.

Specifications

| Capacity | 190L Net / 215L Gross | Power usage | Solid 2.7 kW Glass 3.5 kW / 24 hours |
|---------------------|---|--------------------------------|--|
| Dimensions external | 597w x 645d x 1370h | Air convection | Fan assisted |
| Dimensions internal | 505w x 462d x 1025h | Temperature range | 1°C to +10°C |
| Door | Solid and Glass available Reversible | Controller | Microprocessor with external LCD graphic display |
| Weight | Solid 58kg / Glass 65kg | Interior/Exterior | (HIPS) High impact polystyrene |
| Shelves fitted | 5 | Temperature resolution | 0.1°C |
| Castors | 2 wheels rear, 2 adjustable feet front | Temperature fluctuation at 4°C | +/- 0.5°C |
| Internal light | Yes | Refrigerant | R134A |
| Door Open Alarm | Yes | Power | 230V / 50Hz |
| Noise Level dB | 45.6 | | |